

# WS10S-3000, Pedestrian stacker 1000 kg



Article no: 1615045104

The WS 10 model is a nimble, easily maneuvered stacker without platform. Equipped with a long control arm and ergonomic handle for safe and comfortable work.

- -Travel speed: 3.5 km/h laden, 4 km/h unladen
- -Min. turning radius: 1430 mm
- -Lifting speed: 95 mm/s laden, 134 mm/s unladen
- -Lowering speed: 130 mm/s laden, 94 mm/s unladen
- -Max. gradient: 5% laden, 7% unladen
- -Load center: 600 mm

Electronics/Motor:

- Drive motor: 0,65 kW
- Electromagnetic brake
- Lift motor: 1,5 kW
- Battery voltage/capacity(20h): 2x(12V/85Ah)
- Battery size, mm: 2x(260x169x215)
- Control system: 1212P-2501(CURTIS)

Capacity/kg:	1000
Length / Depth (mm):	1740
Width (mm):	820
Height (Min.) (mm):	2035
Height (mm):	3500
Fork length (mm):	1120
fork width (mm):	160
Fork height/thickness (mm):	55
Inner/other dimensions LxWxH (mm):	-Lift height: 90-3000 mm -Total width over forks (outer edges): 560 mm -Height of rear section (pump/electronics unit): 760 mm -Ground clearance: 30 mm
Weight (kg):	515
Color:	Red (RAL 3020)/Black
Material:	Steel/Plastic/Polyurethane wheels
Wheel data (Standard- /Steering wheels):	-Material, drive wheel: polyurethane -Diameter, drive wheel: 220 mm -Material, balance wheel: polyurethane -Diameter, balance wheel: 124 mm
Wheel data (Fork wheels):	-Quantity: 4 (bogie) -Material: polyurethane -Diameter: 78 mm